

NORDEL[™] 6565 XFC Hydrocarbon Rubber Hydrocarbon Rubber

Overview

NORDEL 6565 XFC is an amorphous EPDM grade designed for extruded applications. It is ideally suited for solid and foamed extruded profiles requiring fast cure conditions. The combination of high viscosity and low crystallinity allows for good balance of processability, extensibility, low-temperature properties and performance. The product features improved mixing and extrusion characteristics, suitable for class A surface manufacturing with improved shape stability of the green compound.

Main Characteristics:

- Amorphous
- High diene
- High molecular weight
- · Good low temperature properties

Applications:

- Extruded profiles
- Coolant hoses

Complies with:

• U.S. FDA 21 CFR 175.105 (See NOTES),

Consult the regulations for complete details.

NOTES:

(1) Adhesives only.

Physical	Nominal Value	(English)	Nominal Value	(SI)	Test Method
Density	0.862	g/cm³	0.862	g/cm³	ASTM D297
Ethylene Content	55.0	wt%	55.0	wt%	ASTM D3900
Ethylidene Norbornene (ENB) Content	8.5	wt%	8.5	wt%	ASTM D6047
Mooney Viscosity (ML 1+4, 257°F (125°C))	65	MU	65	MU	ASTM D1646
Ash Content	< 0.1	wt%	< 0.1	wt%	ASTM D296
Molecular Weight Distribution	Broad		Broad		Dow Method
Propylene Content	36.5	wt%	36.5	wt%	ASTM D3900
Residual Transition Metal	< 10	ppm	< 10	ppm	Dow Method
Volatile Matter	< 0.40	wt%	< 0.40	wt%	Dow Method

Storage and Handling:

The quality of EPDM products may be affected by exposure to artificial or natural light. This product should be stored indoors in its original packaging and out of direct sunlight.

Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

Product Stewardship	The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products – from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.						
Customer Notice	Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.						
Medical Applications Policy	 NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service ("Product") into any commercial or developmental application that is intended for: a. long-term or permanent contact with internal bodily fluids or tissues. "Long-term" is contact which exceeds 72 continuous hours; b. use in cardiac prosthetic devices regardless of the length of time involved ("cardiac prosthetic devices" include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices); c. use as a critical component in medical devices that support or sustain human life; or d. use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction. Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS. 						
Disclaimer	NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.						
	NOTICE: This data is based on information Dow believes to be reliable, as demonstrated in controlled laboratory testing. They are offered in good faith, but without guarantee, as conditions and method of us of Dow products are beyond Dow's control. Dow recommends that the prospective user determine the suitability of these materials and suggestions before adopting them on a commercial scale.						
	To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability for the accuracy and completeness of such information.						
Additional	North America		Europe/Middle East	+800-3694-6367			
Information	U.S. & Canada:	1-800-441-4369 1-989-832-1426	Italy:	+31-11567-2626 +800-783-825			
	Mexico:	+1-800-441-4369	itary.	1000-700-020			
	Latin America Argentina: Brazil: Colombia:	+54-11-4319-0100 +55-11-5188-9000 +57-1-219-6000	South Africa Asia Pacific	+800-99-5078			
	Mexico:	+52-55-5201-4700		+603-7965-5392			
www.dowplastics.com	This document is intended for	r use within Asia Pacifi	c, Europe, Latin America, North Amer	rica			
	Published: 2016-12-09						
	© 2019 The Dow Chemical C	Company					

